



The Sound Choice  
for Leak Detection.™

fluidconservation.com

(800) 531-5465

1960 Old Gatesburg Road, Suite #150  
State College, PA 16803

# Tri-Corr Touch Pro

## High Performance Correlator

### Control

Temperature Range	-20 to 50°C (4 to 120°F)
Antenna	External - magmount
Battery Life	12 hours (rechargeable in case)
Dimensions	H = 90mm, W = 250mm, D = 180mm
Weight	1.9kg
Environmental	IP65
Battery Life	Typically 3 years (depending on settings and signal condition)

### Outstation

Connections	Headphones, external antenna, charging
Battery Life	12 hours (rechargeable)
Battery Type	Rechargeable lithium batteries
Weight	700g
Antenna	External antenna (optional)
Dimensions	H = 200mm, W = 135mm, D = 50mm
Weight	870g
Environment	IP65



### Key Features and Benefits

- **Automatic Intelligent Filtering System:** Automatically optimizes filters for the best results.
- **Resistive Color Touch Screen:** Features clear, multifunctional graphics for user convenience and compatibility with gloves.
- **Portable and Durable:** Compact design built with robust materials for reliable use in demanding environments.
- **Flexible Charging Options:** Supports charging via mains power or a 12V vehicle supply, even while in its case.

All images, text, and designs are protected by US copyright law and remain the property of FCS. Copying or using any content from FCS's website or literature without the written consent of FCS is against the law. FCS reserves the right to vary the specification.

